

**TESTING APPLICATION STANDARD (TAS) No. 112-95
Appendix A**

CLARIFICATION OF TESTING FREQUENCY AND SAMPLING METHOD

- 1. Scope:**
 - 1.1 The purpose of this Appendix is to define frequency of testing and method of sampling.
 - 4.3 The frequency of testing shall be per 250,000 tiles delivered or quarterly, whichever is more frequent.

- 2. Definitions:**
 - 2.1 *Domestic Manufacturers:* Those companies whose tiles are manufactured in the United States.
 - 2.2 *Import Manufacturers:* Those companies whose tiles are manufactured outside the United States.

- 3. Domestic Manufacturers:**
 - 3.1 For tile lots in excess of 250,000 tiles, sampling shall be in accordance with Table 3 of TAS 112.
 - 3.2 Tile samples shall be taken from tile inventories over 28 days old such that all tiles have an equal chance of being selected; or
 - 3.3 Tile samples may be randomly selected from the manufacturing line and conditioned at the test lab for 28 days.
 - 3.4 Testing shall be conducted quarterly. All sampling, testing and calculations shall be conducted by an approved testing agency. All test results, including calculations, shall be signed by a professional engineer or registered roof consultant.

- 4. Import Manufacturers:**
 - 4.1 For tile lots in excess of 250,000 tiles, sampling shall be in accordance with Table 3 of TAS 112.
 - 4.2 Tile samples shall be randomly selected from tile shipments.

FLORIDA BUILDING CODE

2nd DRAFT

COPYRIGHT® ICC 2007