

APPENDIX L

**INTERNATIONAL ONE- AND TWO-FAMILY DWELLING CODE
ELECTRICAL PROVISIONS/NATIONAL ELECTRICAL CODE
CROSS-REFERENCE
Reserved**

This page left intentionally blank.

	Exception 2	Sections 230.42(b) and 230.79
	Exception 3	Sections 230.42(b) and 230.79(A)
E3503.3	Overload protection	Section 230.90
E3503.3.1	Ungrounded conductor	Section 230.90(a)
	Exception	Section 230.90(a), Exception No. 3
E3503.3.2	Not in grounded conductor	Section 230.90(b)
E3503.3.3	Location	Section 230.91
E3503.4	Grounding electrode conductor size	Section 250.66
SECTION E3504	OVERHEAD SERVICE-DROP AND SERVICE CONDUCTOR INSTALLATION	
E3504.1	Clearance from building openings	Section 230.9
Figure E3504.1	Clearances from building openings	Section 230.9
E3504.2	Vertical clearances	Section 230.24
E3504.2.1	Above roofs	Section 230.24(a)
	Exception 1	Section 230.24(a), Exception No. 1
	Exception 2	Section 230.24(a), Exception No. 2
	Exception 3	Section 230.24(a), Exception No. 3
	Exception 4	Section 230.24(a), Exception No. 4
Figure E3504.2.1	Clearances from roofs	Section 230.24
E3504.2.2	Vertical clearance from grade	Section 230.24(b)
	Item 1	Section 230.24(b)
	Item 2	Section 230.24(b)
	Item 3	Section 230.24(b)
E3504.3	Point of attachment	Section 230.26
E3504.4	Means of attachment	Section 230.27
E3504.5	Service masts as supports	Section 230.28
E3504.6	Supports over buildings	Section 230.29
SECTION E3505	SERVICE-ENTRANCE CONDUCTORS	
E3505.1	Insulation of service-entrance conductors	Section 230.41
	Exception 1	Section 230.41, Exception
	Exception 2	Section 230.41, Exception
E3505.2	Wiring methods for services	Section 230.43
E3505.3	Spliced conductors	Section 230.46
E3505.4	Protection against physical damage	Section 230.49
E3505.5	Protection of service cables against damage	Section 230.50(a)
E3505.6	Direct sunlight exposure	Section 310.8(D)
E3505.7	Mounting supports	Section 230.51
E3505.8	Raceways to drain	Section 230.53
E3505.9	Overhead service locations	Section 230.54
E3505.9.1	Rain-tight service head	Section 230.54(a)
E3505.9.2	Service cable, service head or gooseneck	Section 230.54(b)
E3505.9.3	Service head location	Section 230.54(c)
	Exception	Section 230.54(c), Exception
E3505.9.4	Separately bushed openings	Section 230.54(e)
E3505.9.5	Drip loops	Section 230.54(f)
E3505.9.6	Conductor arrangement	Section 230.54(g)
E3505.9.7	Secured	Section 230.54(d)
SECTION E3506	SERVICE EQUIPMENT—GENERAL	
E3506.1	Service equipment enclosures	Section 230.62
E3506.2	Working space	Section 110.26
E3506.3	Available short-circuit current	None
E3506.4	Marking	Section 230.66
SECTION E3507	SYSTEM GROUNDING	
E3507.1	System service ground	Sections 250.20(b)(1) and 250.24(a)
E3507.2	Location of grounding electrode conductor connection	Sections 250.24(a)(1) and (a)(5)

E3507.3	Two or more buildings or structures supplied from a common service	Section 250.32(a)
	Exception	Section 250.32(a), Exception
E3507.3.1	Equipment grounding conductor	Section 250.32(b)(1) and Table 250.122
E3507.3.2	Grounded conductor	Section 250.32(B)(2)
E3507.4	Grounding electrode conductor	Section 250.24(c)
E3507.5	Main bonding jumper	Section 250.28
E3507.6	Common grounding electrode	Section 250.58

SECTION E3508 GROUNDING ELECTRODE SYSTEM

E3508.1	Grounding electrode system	Section 250.50
E3508.1.1	Metal underground water pipe	Section 250.52(a)(1)
E3508.1.2	Concrete-encased electrode	Section 250.502(A)(3)
E3508.1.3	Ground Rings	Sections 250.52(A)(4), 250.52(F)
E3508.1.4	Rod and pipe electrodes	Section 250.52(A)(5)(a)
E3508.1.4.1	Installation	Section 250.53(G)
E3508.1.5	Plate electrodes	Section 250.52(A)(6)
E3508.2	Rod, pipe and plate electrode requirements	Section 250.53(G)
E3508.3	Resistance of rod, pipe and plate electrodes	Section 250.56
E3508.5	Metal underground gas piping system	Section 250.52(B)

SECTION E3509 BONDING

E3509.1	General	Section 250.90
E3509.2	Bonding of service equipment	Section 250.92(a)
E3509.3	Bonding to other systems	Section 250.94
E3509.4	Method of bonding at the service	Section 250.92(B)
E3509.4.1	Grounded service conductor	Section 250.94(1)
E3509.4.2	Threaded connections	Section 250.94(2)
E3509.4.3	Threadless couplings and connectors	Section 250.94(3)
E3509.4.4	Other devices	Section 250.94(4)
E3509.5	Sizing bonding jumper on supply side of service and main bonding jumper	Section 250.102(C)
E3509.6	Metal water piping bonding	Section 250.104(A)
E3509.7	Bonding other metal piping	Section 250.104(B)

SECTION E3510 GROUNDING ELECTRODE CONDUCTORS

E3510.1	Installation	Section 250.64(A) and (B)
E3510.2	Enclosures for grounding electrode conductors	Section 250.64(E)

SECTION E3511 GROUNDING ELECTRODE CONDUCTOR CONNECTION TO GROUNDING ELECTRODES

E3511.1	Methods of grounding connection to electrodes	Section 250.70
E3511.2	Accessibility	Section 250.68(A)
E3511.3	Effective grounding path	Section 250.68(B)
E3511.4	Protection of ground clamps and fittings	Section 250.10
E3511.5	Clean surfaces	Section 250.12

CHAPTER 36 BRANCH CIRCUIT AND FEEDER REQUIREMENTS

SECTION E3601 GENERAL

E3601.1	Scope	None
E3601.2	Branch-circuit and feeder ampacity	Sections 210.19(A) and 215.2(A)(1)
E3601.3	Selection of ampacity	Section 310.15(A)(2)
E3601.4	Multioutlet branch circuits	Section 210.19(A)(2)
E3601.5	Multiwire branch circuits	Section 210.4

SECTION E3602 BRANCH CIRCUIT RATINGS

E3602.1	Branch-circuit voltage limitations	Sections 210.6(A) and (B)
E3602.2	Branch-circuit ampere rating	Section 210.3
E3602.3	Fifteen- and 20-ampere branch circuits	Section 210.23(A)
E3602.4	Thirty-ampere branch circuits	Section 210.23(B)
E3602.5	Branch circuits serving multiple loads or outlets	Section 210.23(A)
E3602.6	Branch circuits serving a single motor	Section 430.22(A)

E3602.7	Branch circuits serving motor-operated and combination loads	Section 220.4(A)
E3602.8	Branch-circuit inductive lighting loads	Section 220.4(B)
E3602.9	Branch-circuit load for ranges and cooking appliances	Table 220.19, Note 4
E3602.9.1	Minimum branch circuit for ranges	Section 210.19(A)(3)
E3602.10	Branch circuits serving heating loads	Sections 422.13 and 424.3(A)
E3602.11	Branch circuits for air-conditioning and heat pump equipment	Sections 440.35, 440.4(B) and 440.62(A)
E3602.12	Branch circuits serving room air conditioners	Section 440.62(A)
E3602.12.1	Where no other loads are supplied	Section 440.62(B)
E3602.12.2	Where lighting units or other appliances are also supplied	Section 440.62(C)
E3602.13	Branch-circuit requirement—summary	Sections 210.24 and 210.25
Table E3602.13	Branch-circuit requirement—summary	Table 210.24

SECTION E3603

REQUIRED BRANCH CIRCUITS

E3603.1	Branch circuits for heating	Sections 422.12 and 422.12 Exception
E3603.2	Kitchen and dining area receptacles	Section 210.52 (B)(1)
E3603.3	Laundry circuit	Sections 210.23(A) Exception and 210.11(C)(2)
E3603.4	Bathroom branch circuits	Section 210.11(C)(3)
E3603.5	Number of branch circuits	Section 210.11(A)
E3603.6	Branch-circuit load proportioning	Section 210.11(B)

SECTION E3604

FEEDER REQUIREMENTS

E3604.1	Conductor size	Table 310.15(B)(6), Sections 215.2 (A)(3), (A)(4) and 220.10(A)
E3604.2	Minimum feeder conductor size	Section 215.2(A)(2)
E3604.3	Feeder loads	Table 220.11
Table E3604.3(1)	Feeder load calculation	Table 220.11, Table 220.30(C), Sections 220.14, 220.15, 220.17, 220.18 and 220.19
Table E3604.3(2)	Demand loads for electric ranges, wall-mounted ovens, counter-mounted cooking units and other cooking appliances over 1 ³ / ₄ kVA rating	Table 220.19
E3604.4	Feeder neutral load	Section 220.22
E3604.5	Lighting and convenience receptacle load	Section 220.3(A), Table 220.3(A)
E3604.6	Ampacity and computed loads	Section 220.10
E3604.7	Feeder and branch-circuit conductors	Section 240.21(A)

SECTION E3605

CONDUCTOR SIZING AND OVERCURRENT PROTECTION

E3605.1	General	Section 310.15(A)
Table E3605.1	Allowable ampacities	Tables 310.16 and 240.4 D
E3605.2	Correction factors for ambient temperatures	Table 310.16
Table E3605.2	Ambient temperature correction factors	Table 310.16, Correction factors
E3605.3	Adjustment factor for conductor proximity	Section 310.15(B)(2)(a)
Table E3605.3	Conductor proximity adjustment factors	Table 310.15(B)(2)(a)
E3605.4	Temperature limitations	Section 110.14(C)
E3605.4.1	Conductors rated 60°C	Section 110.14(C)(1)(a)
E3605.4.2	Conductors rated 75°C	Section 110.14(C)(1)(b)
E3605.4.3	Separately installed pressure connectors	Section 110.14(C)(2)
E3605.4.4	Conductors of type NM cable	Sections 334.80 and 334.112
E3605.5	Overcurrent protection required	Table 310.15(B)(6), Sections 240.4, 240.5, 240.21
E3605.5.1	Cords	Section 240.5
E3605.5.2	Overcurrent devices of the next higher size	Section 240.4(B)
E3605.5.3	Small conductors	Section 240.4(D)
E3605.5.4	Air conditioning and heat pump equipment	Section 240.4(G)
E3605.6	Fuses and fixed trip circuit breakers	Section 240.6
E3605.7	Location of overcurrent devices in or on premises	Sections 240.24(A),(C),(D),(E)
E3605.8	Ready access for occupants	Section 240.24(B)
E3605.9	Enclosures for overcurrent devices	Section 240.30 (A)(B)

SECTION E3606

PANELBOARDS

E3606.1	Panelboard rating	Section 408.13
E3606.2	Panelboard circuit identification	Section 408.4
E3606.3	Panelboard overcurrent protection	Section 408.16(A)

E3606.4	Grounded conductor terminations	Section 408.21
CHAPTER 37 WIRING METHODS		
SECTION E3701 GENERAL REQUIREMENTS		
E3701.1	Scope	Section 300.1
E3701.2	Allowable wiring methods	Sections 110.8 and 300.3
Table E3701.2	Allowable wiring methods	None
E3701.3	Circuit conductors	Section 300.3(B)
E3701.4	Wiring method applications	Chapter 3 and Section 300.2
Table E3701.4	Allowable applications for wiring methods	Chapter 3 and Section 300.2
SECTION E3702 ABOVE-GROUND INSTALLATION REQUIREMENTS		
E3702.1	Installation and support requirements	Chapter 3
Table E3702.1	General installation and support requirements for wiring methods	Chapter 3
E3702.2	Cables in accessible attics	Sections 320.23 and 334.23
E3702.2.1	Across structural members	Sections 320.23(A) and 334.23
E3702.2.2	Cable installed through or parallel to framing members	Sections 320.17, 320.23(A), 334.17, 334.23 and 300.4(B)
E3702.3	Exposed cable	Sections 320.15 and 334.15
E3702.3.1	Surface installation	Section 334.15
E3702.3.2	Protection from physical damage	Section 334.15(B)
E3702.3.3	Locations exposed to direct sunlight	Section 310.8(D)
E3702.4	In unfinished basements	Section 334.15(C)
E3702.5	Bends	Sections 320.24 and 334.24
E3702.6	Raceways exposed to different temperatures	Section 300.7(A)
SECTION E3703 UNDERGROUND INSTALLATION REQUIREMENTS		
E3703.1	Minimum cover requirements	Section 300.5(A)
Table E3703.1	Minimum cover requirements, burial in inches	Table 300.5
E3703.2	Warning ribbon	Section 300.5(D)(3)
E3703.3	Grounding	Section 300.5(B)
E3703.4	Protection from damage	Section 300.5(D)
E3703.5	Splices and taps	Section 300.5(E)
E3703.6	Backfill	Section 300.5(F)
E3703.7	Raceway seals	Section 300.5(G)
E3703.8	Bushing	Section 300.5(H)
E3703.9	Single conductors	Section 300.5(I)
E3703.10	Ground movement	Section 300.5(J)
CHAPTER 38 POWER AND LIGHTING DISTRIBUTION		
SECTION E3801 RECEPTACLE OUTLETS		
E3801.1	General	Section 210.50 and 210.52
E3801.2	Convenience receptacle distribution	Section 210.52(A)
E3801.2.1	Spacing	Section 210.52(A)(1)
E3801.2.2	Wall space	Section 210.52(A)(2)
E3801.2.3	Floor receptacles	Section 210.52(A)(3)
E3801.3	Small appliance receptacles	Section 210.52(B)
E3801.3.1	Other outlets prohibited	Section 210.52(B)(2)
E3801.3.2	Limitations	Section 210.52(B)(3)
E3801.4	Countertop receptacles	Section 210.52(C)
E3801.4.1	Wall counter space	Section 210.52(C)(1)
E3801.4.2	Island counter spaces	Section 210.52(C)(2)
E3801.4.3	Peninsular counter space	Section 210.52(C)(3)
E3801.4.4	Separate spaces	Section 210.52(C)(4)
E3801.4.5	Receptacle outlet location	Section 210.52(C)(5)
E3801.5	Appliance outlets	Section 210.50(C)
E3801.6	Bathroom	Section 210.52(D)

E3801.7	Outdoor outlets	Section 210.52(E)
E3801.8	Laundry areas	Section 210.52(F)
E3801.9	Basements and garages	Section 210.52(G)
E3801.10	Hallways	Section 210.52(H)
E3801.11	HVAC outlet	Section 210.63

SECTION E3802 GROUND-FAULT AND ARC-FAULT CIRCUIT-INTERRUPTER PROTECTION

E3802.1	Bathroom receptacles	Section 210.8(A)(1)
E3802.2	Garage receptacles	Section 210.8(A)(2)
E3802.3	Outdoor receptacles	Section 210.8(A)(3)
E3802.4	Crawl space receptacles	Section 210.8(A)(4)
E3802.5	Unfinished basement receptacles	Section 210.8(A)(5)
E3802.6	Kitchen receptacles	Section 210.8(A)(6)
E3802.7	Bar sink receptacles	Section 210.8(A)(7)
E3802.8	Boathouse receptacles	Section 210.8(A)(8)
E3802.9	Electrically heated floors	Section 424.44(G)
E3802.10	Exempt receptacles	Section 210.8(A)(2)
E3802.11	Bedroom outlets	Section 210.12

SECTION E3803 LIGHTING OUTLETS

E3803.1	General	Section 210.70(A)
E3803.2	Habitable rooms	Section 210.70(A)(1)
E3803.3	Additional locations	Section 210.70(A)(2)
E3803.4	Storage or equipment spaces	Section 210.70(A)(3)

SECTION E3804 GENERAL INSTALLATION REQUIREMENTS

E3804.1	Electrical continuity of metal raceways and enclosures	Section 300.10
E3804.2	Mechanical continuity—raceways and cables	Section 300.12
E3804.3	Securing and supporting	Section 300.11(A)
E3804.3.1	Prohibited means of support	Section 300.11(C)
E3804.4	Raceways as means of support	Section 300.11(B)
E3804.5	Raceway installations	Section 300.18
E3804.6	Conduit and tubing fill	Section 300.17 and Chapter 9, Table 1
Tables E3804.6(1)- E3804.6(10)	Maximum number of conductors in conduit or tubing	Section 300.17 and Chapter 9, Table 1, Note 1
E3804.7	Air handling—stud cavity and joist spaces	Section 300.22(C), Exception

CHAPTER E3805 BOXES, CONDUIT BODIES, AND FITTINGS

E3805.1	Box, conduit body, or fitting — where required	Section 300.15
E3805.1.1	Equipment	Section 300.15(B)
E3805.1.2	Protection	Section 300.15(C)
E3805.1.3	Integral enclosure	Section 300.15(E)
E3805.1.4	Fitting	Section 300.15(F)
E3805.1.5	Buried conductors	Section 300.15(G)
E3805.1.6	Luminaires	Section 300.15(J)
E3805.1.7	Closed loop	Section 300.15(M)
E3805.2	Metal boxes	Section 314.4
E3805.3	Nonmetallic boxes	Sections 314.3
E3805.3.1	Nonmetallic-sheathed cable and nonmetallic boxes	Section 314.17(C)
E3805.3.2	Securing to box	Section 314.17(C)
E3805.3.3	Conductor rating	Section 314.17(C)
E3805.4	Minimum depth of outlet boxes	Section 314.24
E3805.5	Boxes enclosing flush-mounted devices	Section 314.19
E3805.6	Boxes at luminaire (lighting fixture) outlets	Section 314.27(A)
E3805.7	Maximum luminaire (fixture) weight	Section 314.27(B)
E3805.8	Floor boxes	Section 314.27(C)
E3805.9	Boxes at fan outlets	Section 314.27(D)
E3805.10	Conduit bodies, junction, pull and outlet boxes to be accessible	Section 314.29

E3805.11	Damp or wet locations	Section 314.15(A)
E3805.12	Number of conductors in outlet, device, and junction boxes and conduit boxes.	Section 314.16
E3805.12.1	Box volume calculations	Section 314.16(A)
Table E3805.12.1	Maximum number of conductors in metal boxes	Table 314.16
E3805.12.1.1	Standard boxes	Section 314.16(A)
E3805.12.1.2	Other boxes	Section 314.16(A)(2)
E3805.12.2	Box fill calculations	Section 314.16(B)
E3805.12.2.1	Conductor fill	Section 314.16(B)(1) and Table 314.16
Table E3805.12.2.1	Volume allowance required per conductor.	Table 314.16
E3805.12.2.2	Clamp fill	Section 314.16(B)(2)
E3805.12.2.3	Support fittings fill	Section 314.16(B)(3)
E3805.12.2.4	Device or equipment fill	Section 314.16(B)(4)
E3805.12.2.5	Equipment grounding conductor fill.	Section 314.16(B)(5)
E3805.12.3	Conduit bodies	Section 314.16(C)
E3805.12.3.1	Splices, taps or devices	Section 314.16(C)(2)
SECTION E3806	INSTALLATION OF BOXES, CONDUIT BODIES AND FITTINGS	
E3806.1	Conductors entering boxes, conduit bodies or fittings	Section 314.17
E3806.1.1	Insulated fittings	Section 300.4(F)
E3806.2	Openings	Section 314.17(A), 110.12(A)
E3806.3	Metal boxes, conduit bodies and fittings.	Section 314.17, 314.17(B)
E3806.4	Unused openings	Section 314.17(A), 110.12(A)
E3806.5	In wall or ceiling	Section 314.20
E3806.6	Plaster, gypsum board and plasterboard.	Section 314.21
E3806.7	Exposed surface extensions.	Section 314.22
E3806.8	Supports	Section 314.23
E3806.8.1	Surface mounting	Section 314.23(A)
E3806.8.2	Structural mounting	Section 314.23(B)
E3806.8.2.1	Nails	Section 314.23(B)(1)
E3806.8.2.2	Braces	Section 314.23(B)(2)
E3806.8.3	Mounting in finished surfaces	Section 314.23(C)
E3806.8.4	Raceway supported enclosures without devices or fixtures.	Section 314.23(E)
E3806.8.5	Raceway supported enclosures with devices or fixtures	Section 314.23(F)
E3806.8.6	Enclosures in concrete or masonry	Section 314.23(G)
E3806.9	Covers and canopies.	Section 314.25
E3806.10	Metal covers and plates	Section 314.25(A)
E3806.11	Exposed combustible finish.	Section 314.25(B)
SECTION E3807	CABINETS AND PANELBOARDS	
E3807.1	Enclosures for switches or overcurrent devices.	Section 312.8
E3807.2	Damp or wet locations	Section 312.2(A)
E3807.3	Position in wall.	Section 312.3
E3807.4	Unused openings	Section 312.5(A), 110.12(A)
E3807.5	Conductors entering cabinets.	Sections 300.4(F) and 312.5(B)
E3807.6	Openings to be closed	Section 312.5(A)
E3807.7	Cables	Section 312.5(C)
SECTION E3808	GROUNDING	
E3808.1	Metal enclosures	Section 250.86, 250.110(1)
E3808.2	Equipment fastened in place or connected by permanent wiring methods (fixed)	Section 250.110(I)
E3808.3	Specific equipment fastened in place or connected by permanent wiring methods	Sections 250.112(J), 250.112(L)
E3808.4	Performance of fault current path.	Section 250.4(A)(5)
E3808.5	Earth as a grounding conductor	Section 250.4(A)(5)
E3808.6	Load-side neutral.	Section 250.142 (B)
E3808.7	Load-side equipment	Section 250.142 (B)
E3808.8	Types of equipment grounding conductors.	Section 250.118
E3808.8.1	Flexible metal conduit.	Section 250.118(6)

E3808.8.2 Liquid-tight flexible metal conduit Section 250.118(7)

E3808.8.3 Nonmetallic sheathed cable (Type NM) Section 334.10(B)

E3808.9 Equipment fastened in place or connected by permanent wiring methods Section 250.134

E3808.10 Methods of equipment grounding Section 250 Part (VII)

E3808.11 Equipment grounding conductor installation Section 250.120

E3808.12 Equipment grounding conductor size Section 250.122(B)

Table E3808.12 Equipment grounding conductor sizing Table 250.122

E3808.12.1 Multiple circuits Section 250.122(C)

E3808.13 Continuity and attachment of equipment grounding conductors to boxes Section 250.148

E3808.14 Connecting receptacle grounding terminal to box Section 250.146

E3808.15 Metal boxes Section 250.148(A)

E3808.16 Nonmetallic boxes Section 250.148(B)

E3808.17 Clean surfaces Section 250.12

E3808.18 Bonding other enclosures Section 250.96(A)

E3808.19 Size of equipment bonding jumper on load side of service Section 250.102(D)

E3808.20 Installation—equipment bonding jumper Section 250.102(E)

SECTION E3809

FLEXIBLE CORDS

E3809.1 Where permitted Sections 400.7 and 400.8

E3809.2 Loading and protection Section 400.5

Table E3809.2 Maximum ampere load and overcurrent-protection-device rating for flexible cords Section 240.4 and Tables 400.5(A), 240.5(B)(1)

E3809.3 Splices Section 400.9

E3809.4 Attachment plugs Section 400.7(B)

CHAPTER 39

DEVICES AND LIGHTING FIXTURES

SECTION E3901

SWITCHES

E3901.1 Rating and application of snap switches Section 404.14(A)

E3901.2 CO/ALR snap switches Section 404.14(C)

E3901.3 Indicating Section 404.7

E3901.4 Time switches and similar devices Section 404.5

E3901.5 Grounding of enclosures Section 404.12

E3901.6 Access Section 404.48

E3901.7 Wet locations Section 404.4

E3901.8 Grounded conductors Section 404.2(B)

E3901.9 Switch connections Section 404.2(A)

E3901.10 Box mounted Section 404.10(B)

E3901.11 Snap switch faceplates Section 404.9(A)

E3901.11.1 Faceplate grounding Section 404.9(B)

E3901.12 Dimmer switches Section 404.14(E)

SECTION E3902

RECEPTACLES

E3902.1 Rating and type Section 406.2(A)(B)

E3902.1.1 Single receptacle Section 210.21(B)(1)

E3902.1.2 Two or more receptacles Section 210.21(B)(3)

Table E3902.1.2 Receptacle ratings for various size multioutlet circuits Section 210.21

E3902.2 Grounding type Section 406.3(A)

E3902.3 CO/ALR receptacles Section 406.2(C)

E3902.4 Faceplates Section 406.5(B)

E3902.5 Position of receptacle faces Section 406.4(D)

E3902.6 Receptacles mounted in boxes Sections 406.4, 406.4(A), 406.5

E3902.7 Receptacles mounted on covers Section 406.4(C)

E3902.8 Damp locations Section 406.8(A)

E3902.9 Wet locations Section 406.8(B)

E3902.10 Bathtub and shower space Section 406.8(C)

E3902.11 Flush mounting with faceplate Section 406.8(E)

E3902.12 Outdoor installation Section 406.8

SECTION E3903

E3903.1	Energized parts	Section 410.3
E3903.2	Luminaires near combustible material	Section 410.5
E3903.3	Exposed conductive parts	Section 410.18(A)
E3903.4	Screw-shell type	Section 410.47
E3903.5	Recessed incandescent luminaires	Section 410.65(C)
E3903.6	Thermal protection	Section 410.73(E)
E3903.7	High-intensity discharge luminaires	Section 410.73(F)
E3903.8	Wet or damp locations	Section 410.4(A)
E3903.9	Lampholders in wet or damp locations	Section 410.49
E3903.10	Bathtub and shower area	Section 410.4(D)
E3903.11	Luminaires in clothes closets	Section 410.8(A)
Figure E3903.11	Closet storage space	Figure 410.8
E3903.12	Luminaire wiring—general	Section 410.22
E3903.12.1	Polarization of luminaires	Section 410.23
E3903.12.2	Luminaires as raceways	Section 410.31

SECTION E3904**LUMINAIRE INSTALLATION**

E3904.1	Outlet box covers	Section 410.12
E3904.2	Combustible material at outlet boxes	Section 410.13
E3904.3	Access	Section 410.16(B)
E3904.4	Supports	Section 410.15(A)
E3904.5	Means of support	Sections 410.16, 314.27(B), 410.15(A)
E3904.6	Exposed ballasts	Section 410.76(A)
E3904.7	Combustible low-density cellulose fiberboard	Section 410.76(B)
E3904.8	Recessed fixture clearance	Sections 410.66(A)(1),(A)(2)
E3904.9	Recessed fixture installation	Section 410.66(B)

SECTION E3905**TRACK LIGHTING**

E3905.1	Installation	Section 410.101(A)
E3905.2	Fittings	Section 410.101(A)(D)
E3905.3	Connected load	Section 410.101(B)
E3905.4	Prohibited locations	Section 410.101(C)
E3905.5	Fastening	Section 410.104
E3905.6	Grounding	Section 410.105(B)

CHAPTER 40**APPLIANCE INSTALLATION****SECTION E4001****GENERAL**

E4001.1	Scope	Sections 422.1 and 424.1
E4001.2	Installation	Sections 110.3(B) and 422.17
E4001.3	Flexible cords	Section 422.16
Table E4001.3	Flexible cord length	Sections 422.16(B)(1) and (2)
E4001.4	Overcurrent protection	Section 422.11
E4001.4.1	Single nonmotor-operated appliance	Section 422.11(E)
E4001.5	Disconnecting means	Sections 422.30, 422.35 and 424.19
Table E4001.5	Disconnecting means	Sections 422.31(A),(B), 422.35, 424.19, 424.20 and 440.14
E4001.6	Support of ceiling-suspended paddle fans	Section 422.18
E4001.7	Snow-melting and deicing equipment protection	Section 210.8(a)(3) Exception and 426.28

CHAPTER 41**SWIMMING POOLS****SECTION E4101****GENERAL**

E4101.1	Scope	Section 680.1
E4101.2	Definitions	Section 680.2

SECTION E4102**WIRING METHODS FOR POOLS, SPAS, HOT TUBS AND HYDROMASSAGE BATHTUBS**

E4102.1	General	Sections 680.7, 680.23(B), 680.21(C), 680.23(F), 680.21(A), 680.40, 680.42 and 680.43
E4102.2	Flexible cords	Sections 680.22(B)(5), 680.7(A),(B), 680.42, 680.42, 680.21(F)(1)

SECTION E4103 EQUIPMENT LOCATION AND CLEARANCES

E4103.1 Receptacle outlets Section 680.22(A)(6)
 E4103.1.1 Location Section 680.22(A)(1)
 E4103.1.2 Where required Section 680.22.(A)(3)
 E4103.1.3 GFCI protection Section 680.22(A)(5)
 E4103.1.4 Indoor locations Sections 680.43(A) and (A)(1)
 E4103.1.5 Indoor GFCI protection Sections 680.43(A)(2), 680.71
 E4103.2 Switching devices Sections 680.22(C), 680.43(C), 680.72
 E4103.3 Disconnecting means Section 680.12
 E4103.4 Luminaires and ceiling fans Section 680.22(B)
 E4103.4.1 Outdoor location Section 680.22(B)
 E4103.4.2 Indoor location Section 680.22(B)(2)
 E4103.4.3 Existing lighting outlets and luminaires Section 680.22(B)(3)
 E4103.4.4 Indoor spas and hot tubs Section 680.43(B)
 E4103.4.5 GFCI protection Section 680.22(A)(4)
 E4103.5 Overhead conductor clearances Section 680.8
 Table E4103.5 Overhead conductor clearances Table 680.8
 Figure E4103.5 Overhead conductor clearances Figure 680.8
 E4103.6 Underground wiring Section 680.10
 Table E4103.6 Underground wiring Section 680.10

SECTION E4104 BONDING

E4104.1 Bonded parts Sections 680.26(B), 680.42(B) and 680.43(D)(4)
 E4104.2 Parts not required to be bonded Sections 680.42(B), 680.43(D)(4) Exception
 E4104.3 Methods of bonding Sections 680.26(B)(4),680.26(C), 680.42(B) and 680.43(E)

SECTION E4105 GROUNDING

E4105.1 Equipment to be grounded Section 680.6
 E4105.2 Luminaires and related equipment Sections 680.23(F)(1) and (2)
 E4105.3 Nonmetallic conduit Sections 680.23(B)(1), 680.23(B)(2)(b)
 E4105.4 Flexible cords Section 680.23(B)(3)
 E4105.5 Motors Section 680.21(A)(1)
 E4105.6 Panelboards Section 680.25(B),(B)(1)
 E4105.7 Cord-connected equipment Section 680.7
 E4105.8 Other equipment Section 250.1

SECTION E4106 EQUIPMENT INSTALLATION

E4106.1 Transformers Section 680.23(A)(2)
 E4106.2 Ground-fault circuit-interrupters Section 680.5
 E4106.3 Wiring on load side of ground-fault circuit-interrupters and transformers Section 680.23(F)(3)
 E4106.4 Underwater luminaires Sections 680.23(A)(1),(A)(3),(A)(7)
 E4106.4.1 Maximum voltage Section 680.23(A)(4)
 E4106.4.2 Luminaire location Sections 680.23(A)(5),(A)(6)
 E4106.5 Wet-niche luminaires Sections 680.23(B)(1)-(5), 680.23(B)(2), 680.23(B)(3), 680.23(B)(4), 680.23(B)(5)
 E4106.6 Dry-niche luminaires Sections 680.23(C)(1), 680.23(C)(2)
 E4106.7 No-niche luminaires Section 680.23(D)
 E4106.8 Junction boxes and enclosures for transformers or
 ground-fault circuit interrupters Sections 680.24(A) through (E)
 E4106.8.1 Junction boxes Section 680.24(A)
 E4106.8.2 Other enclosures Section 680.24(B)
 E4106.8.3 Protection of junction boxes and enclosures Section 680.24(C)
 E4106.8.4 Grounding terminals Section 680.24(D)
 E4106.8.5 Strain relief Section 680.24(E)
 E4106.9 Underwater audio equipment Section 680.27(A)
 E4106.9.1 Speakers Section 680.27(A)(1)
 E4106.9.2 Wiring methods Section 680.27(A)(2)
 E4106.9.3 Forming shell and metal screen Section 680.27(A)(3)
 E4106.10 Electrically operated pool covers Section 680.27(B)

E4106.11	Electric pool water heaters	Section 680.9
E4106.12	Pool area heating	Section 680.27(C)
E4106.12.1	Unit heaters	Section 680.27(C)(1)
E4106.12.2	Permanently wired radiant heaters	Section 680.27(C)(2)
E4106.12.3	Radiant heating cables prohibited.	Section 680.27(C)(3)
E4106.13	Double insulated pool pumps.	Section 680.21(B)
SECTION E4107	STORABLE SWIMMING POOLS	
E4107.1	Pumps	Section 680.31
E4107.2	Ground-fault circuit-interrupters required	Section 680.32
E4107.3	Luminaires	Section 680.33
E4107.3.1	Fifteen (15) volts or less	Section 680.33(A)
E4107.3.2	Not over 150 volts	Section 680.33(B)
SECTION E4108	SPAS AND HOT TUBS	
E4108.1	Ground-fault circuit-interrupters.	Section 680.44
E4108.2	Electric water heaters.	Section 680.9
E4108.3	Underwater audio equipment.	Section 680.43(G)
SECTION E4109	HYDROMASSAGE BATHTUBS	
E4109.1	Ground-fault circuit-interrupters.	Section 680.71
E4109.2	Other electric equipment	Section 680.72
E4109.3	Accessibility	Section 680.73
E4109.4	Bonding.	Section 680.74
CHAPTER 42	CLASS 2 REMOTE CONTROL, SIGNALING, AND POWER-LIMITED CIRCUITS	
SECTION E4201	GENERAL	
E4201.1	Scope.	Section 725.1
E4201.2	Definitions	Article 100 and Section 725.2
SECTION E4202	POWER SOURCES	
E4202.1	Power sources for Class 2 circuits.	Section 725.41(A)
E4202.2	Interconnection of power sources	Section 725.41(B)
SECTION E4203	WIRING METHODS	
E4203.1	Wiring methods on supply side of Class 2 power source	Section 725.51
E4203.2	Wiring methods and materials on load side of the Class 2 power source.	Sections 725.52, 725.61, 725.71, Table 760.61
E4203.2.1	Type CL2P cables.	Section 725.71(A)
E4203.2.2	Type CL2 Cables	Section 725.71(C)
E4203.2.3	Type CL2X Cables.	Sections 725.61(E) and 725.71(D)
E4203.2.4	Marking.	Section 725.71(H)
SECTION E4204	INSTALLATION REQUIREMENTS	
E4204.1	Separation from other conductors.	Section 725.55
E4204.2	Other applications	Section 725.55(J)
E4204.3	Class 2 circuits with communication circuits.	Section 725.56(D)
E4204.4	Class 2 cables with other circuit cables.	Section 725.56(E)
E4204.5	Installation of conductors and cables	Sections 725.5, 725.6, 725.58, 300.11(B)(2)